

Getac recommends Windows 11 Pro for business





- 11th Generation Intel[®] Core[™] i7 / i5 vPro[®] Processor
- Thunderbolt™ 4 brings lightning speed and performance
- ATEX & IECEx explosive atmosphere certified
- Enhanced enterprise security with optional Intel[®] vPro[®], Windows Hello face-authentication camera, TPM 2.0 and many more multi-factor authentication options
- Optional 1D/2D imager barcode reader and HF RFID reader





SPECIFICATIONS

Generation G6

Operating System Windows 11 Pro

Mobile Computing Platform Options

Intel[®] Core™ i5-1135G7 Processor Max. 4.2GHz with Intel[®] Turbo Boost - 8MB Intel[®] Smart Cache

Platform Options: Intel[®] Core™ i5-1145G7 vPro[®] Processor Max. 4.4GHz with Intel[®] Turbo Boost - 8MB Intel[®] Smart Cache

Intel[®] Core™ i7-1165G7 Processor Max. 4.7GHz with Intel® Turbo Boost Technology - 12MB Intel[®] Smart Cache

Intel[®] Core[™] i7-1185G7 vPro[®] Processor Max. 4.8GHz with Intel® Turbo Boost Technology - 12MB Intel[®] Smart Cache

VGA Controller Intel[®] UHD Graphics

Display 11.6" Wide Viewing Angle TFT LCD FHD (1920 x 1080)

1,000 nits LumiBond[®] display with Getac sunlight readable technology

Storage & Memory 8GB DDR4

Optional: 16GB / 32GB DDR4 256GB PCIe NVMe SSD Optional: 512GB / 1TB / 2TB PCIe NVMe SSD

Keyboard

Power button 4 tablet programmable buttons

Pointing Device

Touchscreen Dual mode touchscreen (multi-touch and diaitizer)

Expansion Slots

Optional: Smart card reader Optional: 1D/2D imager barcode reader, or USB 2.0 port, or LAN (RJ45), or serial port + LAN (RJ45) Optional ": HF RFID Reader, or Fingerprint Reader

I/O Interface

5M webcam x 1 ^{III} 8M pixels auto focus rear camera x 1 Audio in/out combo x 1 DC in Jack x 1 USB 3.2 Gen 2 Type-A x 1 Thunderbolt™ 4 Type-C x 1 Optional: SIM card slot x 1 (Micro-SIM, 3FF) ^v Optional: Windows Hello face-authentication FHD camera (front-facing) x 1

Communication Interface

Intel[®] Wi-Fi 6 AX201, 802.11ax Bluetooth (v5.2)[™] Optional: 4G LTE mobile broadband with integrated GPS Optional: 5G Sub-6 with integrated L1/L5 GPS vi,

Optional: 10/100/1000 base-T Ethernet

(Occupies expansion slot)

Security Features TPM 2.0

Kensington lock Optional: Intel[®] vPro[®] Technology Optional: HF RFID Reader[#], or Smart Card Reader Optional: Windows Hello face-authentication FHD camera (front-facing) x 1

Power

AC Adapter(90W, 100-240VAC, 50/60Hz) Li-ion battery(11.4V,typical 2680mAh;min. 2640mAh) x 2 Optional: High capacity Li-ion battery (11.1V, typical 4200mAh; min.4080mAh) x 2

Dimension (W x D x H) & Weight 314 x 224 x 25mm (12.4" x 8.82" x 0.98")

1.58kg (3.48lbs)

Rugged Features MIL-STD-810H certified

IP66 certified Vibration & 4ft (1.2m) drop resistant ATEX & IECEx certified

Environmental Specifications

Temperature ^{viii}: - Operating: -21°C to 60°C / -6°F to 140°F - Storage: -51°C to 71°C / -60°F to 160°F Humidity: - 95% RH, non-condensing

Explosion Protection ATEX/IECEx Zone 2/22 Ex II 3G Ex ic op is IIC T4 Gc Ex II 3D Ex ic op is IIIC T130°C Dc

Pre-installed software

Getac Utility Getac Camera Getac Geolocation Getac Barcode Manager ^{ix} Getac Driving Safety Utility (trial version) Getac KeyWedge Barcode Reader Utility (trial version)

Optional: Absolute Persistence®

Optional software

Getac Driving Safety Utility Getac KeyWedge Barcode Reader Utility Getac Device Monitoring System (GDMŚ) Getac VGPS Utility

Accessories

Battery (11.4V, typical 2680mAh; min. 2640mAh) AC adapter (90W, 100-240VAC, 50 / 60Hz) Digitizer pen

Optional:

Carry bag Battery (11.4V, typical 2680mAh; min. 2640mAh) High capacity Li-ion battery (11.1V, typical 4200mAh; min.4080mAh) Multi-Bay charger (Dual-Bay) Multi-Bay charger (Eight-Bay) AC adapter (90W, 100-240VAC, 50 / 60Hz) Digitizer pen Protection film Hard handle Hand strap Shoulder strap (2-point) Shoulder harness (4-point; handsfree)

Bumper-to-Bumper warranty Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime. That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs. Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days.

Standard

3 years Bumper-to-Bumper

F110-EX FULLY **RUGGED TABLET**

- I. П.
- Ш.
- 1D/2D imager barcode reader, or USB (USB 2.0) port, or Serial port + LAN are mutually exclusive options. 13.56MH2 Contactless HF RFID reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant). 5M webcam and optional Windows Hello face-authentication FHD camera (front-facing) are mutually exclusive options. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area. Units with 4G LTE option come with an embedded SIM card slot. One physical SIM card slot and one eSIM. Network service may vary depending on local telecommunication providers. Weight and dimensions vary from configurations and optional accessories; optional high-capacity batteries add approx. 6mm (H), 0.24kg. Tested by an independent third-party test lab following MIL-STD-810H. Available when barcode reader option is selected. Models require either embedded or standalone GPS module. Factory option. Not user swappable. Support GPS. GLONASS. Gailleo. BeiDou and OZSS IV.
- V. VI
- VII
- VIII.
- IX.
- Х. XI.
- Factory option. Not user swappable. Support GPS, GLONASS, Galileo, BeiDou and QZSS

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.

Getac

Getac House, Stafford Park 12, Telford, Shropshire TF3 3BJ, United Kingdom Tel : +44 (0) 1952 207 222 Sales-Getac-UK@getac.com I www.getac.com/en/ Copyright © 2022 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved. Information provided herewith is for reference only, available specification shall be subjected to quotation by request.